

KEL-DPZ-HD hygienic multi-membrane cable entry plates, round

with metric threads M32 - M63 / IP66 / IP68, FDA compliant



The new cable entry plates KEL-DPZ-HD with metric thread from M32 to M63 have been developed for installation in food processing and packaging machines.

During the development according to the Hygienic Design guidelines, care was taken to ensure that the visible side of the cable entry plate are free of dirt-collecting recesses. The surface was kept very smooth ($Ra = 0,421 \mu\text{m}$ acc. to ISO 4287). The outer contour has a radius of 6 mm instead of the required 3 mm. In addition, the KEL-DPZ-HD uses an FDA-compliant elastomer in accordance with food approval 1935/2004/EG and (EU) 10/2011. The signal colour blue ensures a clear visual colour recognition.

The cable entry plates are designed to route several cables and hoses with a diameter range of 3.2 mm to 22.2 mm and seal them acc. to IP65/66/67/68. A significant advantage over cable glands is the significantly higher cable density and the flexibility of the cable diameter range. The fixation is very simple with the locknut.

IP54

IP55

IP64

IP65

IP66

IP67

IP68

Made in Germany

FDA

1935/
2004/
EG

EU VO.
10/2011

ECOLAB
certified



RoHS
compliant

REACH
COMPLIANCE

UL
US


Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Material	Elastomer Base frame: Polyamide
Flame class	UL94-HB
Operating temperature	-40 C° to 80 C°
Properties	silicone free, halogen free, resistant to oil and mould, higher chemical resistance

Advantages & benefits


- Elastomer of the cable entry plate made of material according to 1935/2004/EG, (EU) 10/2011
- FDA compliant
- Developed according to hygienic design guidelines (EHEDG)
- Hygienic design - free of dirt-collecting recesses
- Ecolab certified
- Very flat design
- Very smooth surface ($Ra = 0,421 \mu\text{m}$ acc. to ISO 4287)
- Very fast assembly
- Cable diameter 3,2 - 22,2 mm
- Very large sealing areas and clamping areas
- High cable density
- Dual sealing of cables (IP66/IP68)
- Suitable for metric cut-outs
- Reproducible cleaning process
- Very low moisture absorption
- High resistance to aromatic solvents, oils, greases, mineral products
- No corrosion possible because plastics have been processed
- Maintenance free
- Hexagonal locknut included in the delivery

Product types & sizes

KEL-DPZ-HD 32|4


Part No. **70351**
 EAN **4251269322785**
 Package quantity **5**
 For max. no. of cables **4**
 Max. cable diameter **12,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **44 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M32**
 Cut-out size, round **32,3 mm**
 Thread **M32 × 1,5**
 Thread length **14 mm**
 Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm

KEL-DPZ-HD 32|4-2


Part No. **70352**
 EAN **4251269322792**
 Package quantity **5**
 For max. no. of cables **4**
 Max. cable diameter **9,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **44 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M32**
 Cut-out size, round **32,3 mm**
 Thread **M32 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 5 - 9.5 mm**

KEL-DPZ-HD 32|7


Part No. **70353**
 EAN **4251269322808**
 Package quantity **5**
 For max. no. of cables **7**
 Max. cable diameter **6,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **44 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M32**
 Cut-out size, round **32,3 mm**
 Thread **M32 × 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ-HD 40|8


Part No. **70354**
 EAN **4251269322815**
 Package quantity **5**
 For max. no. of cables **8**
 Max. cable diameter **10,2 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **52 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M40**
 Cut-out size, round **40,4 mm**
 Thread **M40 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ-HD 50|8

Part No. **70355**
 EAN **4251269322822**
 Package quantity **5**
 For max. no. of cables **8**
 Max. cable diameter **12,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **62 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M50**
 Cut-out size, round **50,4 mm**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm


KEL-DPZ-HD 50|10

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Height
Mounting height

70356
4251269322839
5
10
22,2 mm
22 mm
8 mm

Colour
External diameter
Surface roughness (ISO 4287)
Cut-out size, metric
Cut-out size, round
Thread
Thread length
Clamping range

blue (similar RAL 5005)
62 mm
Ra = 0,421 µm
M50
50,4 mm
M50 × 1,5
14 mm
7 x 3.2 - 6.5 mm
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm


KEL-DPZ-HD 50|12

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Height
Mounting height

70357
4251269322846
5
12
10,2 mm
22 mm
8 mm

Colour
External diameter
Surface roughness (ISO 4287)
Cut-out size, metric
Cut-out size, round
Thread
Thread length
Clamping range

blue (similar RAL 5005)
62 mm
Ra = 0,421 µm
M50
50,4 mm
M50 × 1,5
14 mm
4 x 3.2 - 6.5 mm
8 x 5 - 10.2 mm


KEL-DPZ-HD 50|19

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Height
Mounting height

70358
4251269322853
5
19
6,5 mm
22 mm
8 mm

Colour
External diameter
Surface roughness (ISO 4287)
Cut-out size, metric
Cut-out size, round
Thread
Thread length
Clamping range

blue (similar RAL 5005)
62 mm
Ra = 0,421 µm
M50
50,4 mm
M50 × 1,5
14 mm
19 x 3.2 - 6.5 mm


KEL-DPZ-HD 63|9

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Height
Mounting height

70359
4251269322860
5
9
22,2 mm
22 mm
8 mm

Colour
External diameter
Surface roughness (ISO 4287)
Cut-out size, metric
Cut-out size, round
Thread
Thread length
Clamping range

blue (similar RAL 5005)
75 mm
Ra = 0,421 µm
M63
63,4 mm
M63 × 1,5
14 mm
1 x 3.2 - 6.5 mm
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm


KEL-DPZ-HD 63|13

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Height
Mounting height

70360
4251269322877
5
13
16,2 mm
22 mm
8 mm


Colour
External diameter
Surface roughness (ISO 4287)
Cut-out size, metric
Cut-out size, round
Thread
Thread length
Clamping range

blue (similar RAL 5005)
75 mm
Ra = 0,421 µm
M63
63,4 mm
M63 × 1,5
14 mm
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm



Part No. **70361**
 EAN **4251269322884**
 Package quantity **5**
 For max. no. of cables **14**
 Max. cable diameter **10,2 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **75 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M63**
 Cut-out size, round **63,4 mm**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **14 x 5 - 10.2 mm**



Part No. **70362**
 EAN **4251269322891**
 Package quantity **5**
 For max. no. of cables **35**
 Max. cable diameter **6,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **75 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M63**
 Cut-out size, round **63,4 mm**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **35 x 3.2 - 6.5 mm**